



Swiss-Shield® ULTIMA_ARBOR™ | Shielding fabric | Width 250 cm | 1 meter

From Swiss Shield®. Semitransparent fabric made from LENZING™ ECOVERO™ viscose. Only dry cleaning. Ecru-white. 42 dB. Width 250 cm.



YSHIELD GmbH & Co. KG
94099 Ruhstorf, Germany
www.yshield.com
info@yshield.de

Properties

ULTIMA_ARBOR™ by Swiss-Shield® is made from LENZING™ ECOVERO™ viscose. With its very high shielding performance and renowned excellent hand feel, it once again proves that Swiss-Shield® is a global pioneer in technical shielding fabrics.

EU Ecolabel certified

ULTIMA_ARBOR™ from Swiss-Shield® consists of 82 % ECOVERO™ fibers from LENZING™, which are EU Ecolabel certified.

OEKO-TEX® STANDARD 100

If a textile article carries the **OEKO-TEX® STANDARD 100** label, you can **be certain that the article therefore is harmless for human health.** In many cases the limit values for the STANDARD 100 go beyond national and international requirements. The criteria catalog is updated at least once a year and expanded with new scientific knowledge or statutory requirements. **ZH015208475 OEKO-TEX® Label Check**

Swiss Shield® Shielding fabrics

This fabric is manufactured by Swiss Shield® in Switzerland with a patented, **invisible high-tech yarn.** At YSHIELD we value the constantly high quality of the fabrics - it's not for nothing that we are the world's largest Swiss Shield® distributor.

Technical data

- **Width: 250 cm, +/- 2 cm**
- Length: Available by the meter
- **Attenuation: 42 dB**, two-layer 54 dB
- Color: Ecru-White
- Raw materials: 82 % viscose, 17 % copper, 1 % silver
- Weight: 70 g/m²
- Dimension stability: +/- 3 %

Care instructions

- **This fabric must NOT BE WASHED IN A WASHING MACHINE. A PROFESSIONAL DRY CLEANING P at a dry cleaner with experience with VISCOSE is recommended. The care instructions can be found above in the downloads.**
- DO NOT wash with water
- NO hand wash
- DO NOT tumble dry
- DO NOT bleach
- Iron without steam at degree 1

Shielding attenuation HF & LF

This product **shields high frequency electromagnetic fields (HF)**. Unless otherwise stated, the indicated dB-values apply to 1 GHz. Measurement from 600 MHz to 40 GHz according to standards ASTM D4935-10 or IEEE Std 299-2006.

This product contains electrically conductive parts on the inside which can neither be contacted nor grounded. That's why individual areas **do not shield low frequency electrical fields (LF)**. In case this product is used as a Faraday cage (complete shielding on six sides), there will be no low frequency electrical fields (LF) on the inside, which can be proven with a potential free measurement.

Laboratory & expert report of shielding attenuation up to 40 GHz

We have already invested in our **own professional EMV laboratory** years ago. We not only use it to create our laboratory screening reports but also to check each batch daily. Additionally, we have all our products checked by an **independent, well-respected expert.** Double checked for twice the safety. **Please find the reports above at the downloads.**